



Gulf Merit

Premium oil for pneumatic rock drill and tool lubrication

Product Description

Gulf Merit series are premium quality oils specially developed for the lubrication of pneumatically operated rock drills and other air operated percussion tools. These oils are blended from high quality mineral oils and unique combination of superior film strength, tackiness and anti-wear additives. These oils provide excellent chemical stability and protection against wear, rust and corrosion. These oils have good adhesiveness and preferential metal wetting properties that maintain continuous oil film even in presence of water and thereby reduce the negative effects of water, condensed from moisture carried along with the air stream, on wear and corrosion. The combination of these properties along with superior EP characteristics help in providing excellent lubrication leading to long component life. They are available in five ISO viscosity grades viz. ISO VG 46, 100, 150, 220 and 320.

Features & Benefits

- Excellent load carrying capacity and anti-wear protection reduce component wear and prolong equipment life
- Good chemical stability minimises sludge and deposit formation
- Superior metal wetting properties and adhesiveness help adhesion to metal surfaces and protect them from corrosion
- Excellent water emulsification property provides adequate lubrication even in presence of water

Applications

- Pneumatically operated rock drills in underground/surface mining operations and quarry operations
- Pneumatically operated drills and jack hammers in construction of roads and buildings
- Wide variety of heavy-duty pneumatically operated equipment
- Percussion and rotary air-operated tools in industrial operations
- Pneumatic equipment of Gardner Denver, Chicago Pneumatic, Ingersoll-Rand and other manufacturers

Properties mentioned above are typical only and minor variations, which do not affect the product performances, are to be expected in normal manufacturing. The above information is based on past history of the grade only and must not be construed as a guarantee of performance. Follow equipment manufacturer's recommendations for performance level and viscosity grade. The Material Safety Data Sheet for this product is available from your nearest Gulf Distributor. Gulf Oil International

The information contained herein is believed to be correct at time of publication. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of the products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

www.gulfoilltd.com



Specifications, Approvals & Typical Properties

ISO Viscosity grades	100	150	
Typical Properties			
Test Parameters	ASTM Method	Test Values	
Viscosity @ 40 °C, cSt	D 445	100.8	151.1
Viscosity Index	D 2270	98	96
Flash Point, °C	D 92	230	242
Pour Point, °C	D 97	-15	-15
Density @ 15°C, Kg/l	D 1298	0.886	0.893
Rust Test	D 665A/B	Pass	Pass
Demulsibility, 54 °C Oil-Water-Emulsion, ml (60 minutes)	D 1401	0-0-80	0-0-80
Tackiness		Yes	Yes

Properties mentioned above are typical only and minor variations, which do not affect the product performances, are to be expected in normal manufacturing. The above information is based on past history of the grade only and must not be construed as a guarantee of performance. Follow equipment manufacturer's recommendations for performance level and viscosity grade. The Material Safety Data Sheet for this product is available from your nearest Gulf Distributor. Gulf Oil International

The information contained herein is believed to be correct at time of publication. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of the products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

www.gulfoilltd.com