



Gulf Therm 32

Premium quality heat transfer oil

Product Description

Gulf Therm 32 is premium quality heat transfer oil intended for use in closed indirect heating systems. It is formulated from highly refined base stocks to provide excellent oxidation stability and resistance against thermal cracking. It possesses high specific heat and thermal conductivity to provide more rapid heat dissipation and its ability to flow rapidly at low temperatures ensures quick circulation at start-up and reduced risk of local over-heating. Although Gulf Therm 32 is thermally very stable and is capable of offering extended service life without viscosity increase or deposit formation, it should be realised that the working life depends to a considerable extent on the effectiveness of the measures taken to exclude air. Gulf Therm 32 is primarily intended for use in enclosed and sealed heating systems where the maximum bulk oil temperature does not exceed 315 °C.

Features & Benefits

- Excellent thermal and oxidation stability minimises deposit formation and viscosity increase leading to extended service life and reduced downtime
- Exceptional resistance to thermal cracking and decomposition enables this oil to perform well up to a maximum bulk oil temperature of 315 °C with minimal interference with heat transfer capability
- High specific heat and thermal conductivity of this oil provides more rapid heat dissipation
- Superior low temperature fluidity ensures quick circulation at start-up and reduced risk of local over-heating
- Non corrosive to aluminum, steel, copper, brass or bronze
- Non-toxicity of this oil provides easy disposal of used oil

Applications

- Closed, indirect heating and cooling systems equipped with expansion tanks in all kinds of industrial processes operating at bulk oil temperatures up to 315 °C
- Open heating systems provided that the bulk oil temperature does not exceed 180 °C

Specifications, Approvals & Typical Properties

Gulf Therm 32		
Typical Properties		
Test Parameters	ASTM Method	Test Values
Viscosity @ 40 °C, cSt	D 445	32.2
Viscosity Index	D 2270	102
Flash Point, °C	D 92	230
Fire Point, °C	D 92	255
Pour Point, °C	D 97	-12
Copper Corrosion	D 130	1b
Density @ 15°C, Kg/l	D 1298	0.868

Properties mentioned above are typical only and minor variations, which do not affect the product performances, are to be expected in normal manufacturing. The above information is based on past history of the grade only and must not be construed as a guarantee of performance. Follow equipment manufacturer's recommendations for performance level and viscosity grade. The Material Safety Data Sheet for this product is available from your nearest Gulf Distributor. Gulf Oil International

The information contained herein is believed to be correct at time of publication. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of the products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

www.zulfoilltd.com