



# Gulf Pride 4T

## 4-Stroke Motorcycle Oil

### Product Description

**Gulf Pride 4T** is a high quality 4-stroke gasoline engine oil developed specifically to meet the special requirements of air cooled 4-stroke motorcycles. It is blended from highly refined base oils and performance additives to provide protection to engine, gear box and wet clutch used in 4-stroke motorcycles. The product exceeds the international specifications of API SL and JASO MA 2 for 4-stroke motorcycle oils and the requirements of leading global 4-stroke motorcycle manufacturers. It is available in three different viscometrics, SAE 10W-30, SAE 10W-40 AND SAE 20W-50

### Features & Benefits

- Excellent antiwear properties protect vital engine and gear components leading to reduced maintenance costs
- Good thermo-oxidative stability prevents harmful deposit formation and controls oil thickening facilitating extended engine and oil life
- Controlled frictional properties eliminate clutch slippage and improves drivability
- Better detergency/ dispersancy keeps engine cleaner and reduces maintenance costs
- Effective rust and corrosion inhibition property ensures longer life of critical engine components

### Applications

- Recommended for air cooled 4-stroke motorcycle engines where an API SL and JASO MA 2 quality oil is required
- Also suitable for small 4-stroke gasoline engines used in portable generators, pumps, garden machinery and other applications

### Specifications, Approvals & Typical Properties

Meets the following Specifications		20W-50	10W-40	10W-30
API SL		X	X	X
Has the following On File Status				
JASO MA 2		X	X	X
Typical Properties				
Test Parameters	ASTM Method	Typical Values		
Viscosity @ 100 °C, cSt	D 445	19.3	13.87	11.68
Viscosity Index	D 2270	120	122	128
Flash Point, °C	D 92	248	236	228
Pour Point, °C	D 97	-15	-15	-18
TBN, mg KOH/g	D 2896	7.35	7.78	7.35
Density @ 15°C, Kg/l	D 1298	0.89	0.8784	0.8746
Sulphated Ash, %wt	D 874	0.98	0.98	0.98
Color	D 1500	3.0	L 3.0	2.5
API	D 287	28	29.5	30.2

Properties mentioned above are typical only and minor variations, which do not affect the product performances, are to be expected in normal manufacturing. The above information is based on past history of the grade only and must not be construed as a guarantee of performance. Follow equipment manufacturer's recommendations for performance level and viscosity grade. The Material Safety Data Sheet for this product is available from your nearest Gulf Distributor. Gulf Oil International

The information contained herein is believed to be correct at time of publication. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of the products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

[www.gulfoilltd.com](http://www.gulfoilltd.com)