



GULF SUPERFLEET SPECIAL

Commercial Vehicle Engine Oil

Product Description

Gulf Super Fleet Special SAE 25W50 is a multi-grade oil for use in turbocharged & naturally aspirated diesel engines of two and four stroke. The Product is used for vehicles that operate in severe condition. Specially protects the hottest parts of the engine working with a thick oil film that produces a seal and automatically brings down oil consumption and prevents the presence of excessive smoke.

Features & Benefits

- Maintains control over thinning of the lubrication film on the cylinders where you find High temperatures.
- Outstanding thermal and oxidative stability reduces low-temperature sludge build-up, high-temperature deposits and oil thickening.
- Control Rust formation and protects against corrosion.
- Excellent soot handling capability minimizes soot related viscosity increase and leads to longer engine/oil life
- Reduces Cool Start wear and a Superior shear stability maintains viscosity in severe high-temperature service.
- Exceptional TBN retention resists harmful effects of corrosive exhaust gases and extends oil life.

Applications

- Operation in typical City for buses, taxis in addition it is very efficient in High-Way where it demands high-speeds.
- Heavy Duty Diesel Engine in construction, agriculture and other off-highway applications, where continuous halting & Running operation is required.
- High performance gasoline engines and mixed fleet operations.



Specifications, Approvals & Typical Properties

Meets the following Specifications		25W-50
CF/SF		X
Typical Properties		
Test Parameters	ASTM Method	Typical Values
Viscosity @ 100 °C, cSt	D 445	20.34
Viscosity Index	D 2270	123
Flash Point, °c	D 92	240
Pour Point, °C	D 97	-15
TBN, mg KOH/g	D 2896	9.5
Density @ 15°C, Kg/l	D 1298	0.887
Sulphated Ash, %wt	D 874	1.35
Phosphorus, %wt	D 4927	0.07

Properties mentioned above are typical only and minor variations, which do not affect the product performances, are to be expected in normal manufacturing. The above information is based on past history of the grade only and must not be construed as a guarantee of performance. Follow equipment manufacturer's recommendations for performance level and viscosity grade. The Material Safety Data Sheet for this product is available from your nearest Gulf Distributor. Gulf Oil International
The information contained herein is believed to be correct at time of publication. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of the products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.
www.gulfoilltd.com