



Gulf ATF DX III

High performance Automatic Transmission Fluid

Product Description

Gulf ATF DX III is a high performance automatic transmission fluid for all General Motors and Ford automatic transmissions requiring DEXRON[®]-III G or MERCON[®] quality fluids respectively. The specially selected performance additives and base oils in this oil provide improved thermo-oxidative stability, friction retention properties, corrosion & rust protection, foam control and seal compatibility. It exceeds the performance requirements of General Motors DEXRON[®] III G and Ford MERCON[®] specifications.

Features & Benefits

- Improved thermo-oxidative stability, wear protection and resistance to chemical deterioration protect against degradation at high operating temperatures and helps in maintaining the efficiency of the transmission system
- Extremely high Viscosity index ensures adequate lubrication in both high operating & low starting temperatures
- Controlled frictional properties provide smooth transmission and good shift performance
- Better foam control leads to smooth & lasting shift feel and reduces fluid loss
- Provides improved protection against rust and corrosion
- Superior Low temperature pumpability and circulation ensures good cold start performance
- Compatibility with all common seal materials reduces possibility of oil leakage

Applications

- Recommended for all vehicles of Ford requiring MERCON[®] quality fluids and General Motors requiring DEXRON[®]-III G quality fluids.
- Being back serviceable, it is also recommended for automatic transmissions requiring General Motors DEXRON[®] II E or DEXRON[®] II D fluids
- Also recommended for power steering systems, hydraulic applications and certain manual transmissions where such type of fluids are specified

Properties mentioned above are typical only and minor variations, which do not affect the product performances, are to be expected in normal manufacturing. The above information is based on past history of the grade only and must not be construed as a guarantee of performance. Follow equipment manufacturer's recommendations for performance level and viscosity grade. The Material Safety Data Sheet for this product is available from your nearest Gulf Distributor. Gulf Oil International

The information contained herein is believed to be correct at time of publication. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of the products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

www.gulfoilltd.com



Specifications, Approvals & Typical Properties

Meets the following Specifications		
General Motors DEXRON [®] III G ;Allison C-4; ZF TE-ML09		
Ford MERCON [®] :		
Typical Properties		
Test Parameters	ASTM Method	Typical Values
Viscosity @ 100 °C, cSt	D 445	7.9
Viscosity Index	D 2270	168
Flash Point, °C	D 92	184
Pour Point, °C	D 97	-30
Brookfield Viscosity @ -40 °C, cP	D 2983	17900
Density @ 15°C, Kg/l	D 1298	0.865

DEXRON[®] is a registered trademark of General Motors Corporation
MERCON[®] is a registered trademark of Ford Motor Company

Properties mentioned above are typical only and minor variations, which do not affect the product performances, are to be expected in normal manufacturing. The above information is based on past history of the grade only and must not be construed as a guarantee of performance. Follow equipment manufacturer's recommendations for performance level and viscosity grade. The Material Safety Data Sheet for this product is available from your nearest Gulf Distributor. Gulf Oil International

The information contained herein is believed to be correct at time of publication. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of the products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

www.gulfoilltd.com