



Gulf Universal Tractor Transmission Fluid

High performance transmission-hydraulic-wet brake fluid for tractors

Product Description

Gulf Universal Tractor Transmission Fluid series are high performance fluids for use in transmissions, hydraulic systems, oil immersed brakes of tractors and off-road equipment. These fluids are specially designed for use where a common lubricant reservoir serves transmissions, final drives and hydraulic systems and to optimize the performance of agricultural and commercial tractors. These fluids meet the specifications of major equipment manufacturers of tractors.

Features & Benefits

- Enhanced frictional properties optimize clutch performance and ensure noise free operation of wet brakes
- High viscosity index coupled with high shear stability provides consistent performance
- Excellent low temperature fluidity provides good response and effective lubrication at low ambient temperatures
- Robust anti-wear and extreme pressure properties control wear, extend equipment life and reduce maintenance costs
- Multipurpose capability reduces inventory and prevents accidental contamination and misapplication

Applications

- Tractors and other equipment requiring a common fluid to lubricate transmission, differential and hydraulic systems
- Recommended for off high way equipment in agriculture, construction, quarrying
- Caterpillar power shift transmissions requiring a TO-2 fluid
- Can be used in transmission applications requiring API GL-4 oil except in hypoid gear designs.

Properties mentioned above are typical only and minor variations, which do not affect the product performances, are to be expected in normal manufacturing. The above information is based on past history of the grade only and must not be construed as a guarantee of performance. Follow equipment manufacturer's recommendations for performance level and viscosity grade. The

Material Safety Data Sheet for this product is available from your nearest Gulf Distributor. Gulf Oil International

The information contained herein is believed to be correct at time of publication. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of the products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

www.gulfoilltd.com



Specifications, Approvals & Typical Properties

Meets the following Specifications		SAE 85W
API GL-4, Eaton Vickers 35VQ25		X
Ford M2C41B, M2C48-B/C, M2C86-B/C, M2C134D, White (Q-1705, 1722, 1766, 1766B, 1802, 1826)		X
Massey Ferguson 1129A, 1127 A/B		X
Massey Ferguson M1110, M1135, M1141, M1143, M1145		X
John Deere J 14 A/B/C, J 20C, J 20D, J 21A		X
Allison C-3, C-4, Sauer Sunstrand/ Danfoss (Hydrostatic trans fluid)		X
J.I. Case/ Case International (MS-1204, 1205, 1206, 1207, 1209, 1210, JIC-143, 144, 145, 185)		X
Caterpillar TO-2, Denison (HF-0, 1, 2), Kubota (UDT Fluid)		X
Typical Properties		
Test Parameters	ASTM Method	Typical Values
Viscosity @ 100 °C, cSt	D 445	11.0
Viscosity Index	D 2270	130
Flash Point, °C	D 92	224
Pour Point, °C	D 97	-15
Density @ 15°C, Kg/l	D 1298	0.8874
Brookfield Viscosity, cP (@ -18 °C)	D 2983	3850

Properties mentioned above are typical only and minor variations, which do not affect the product performances, are to be expected in normal manufacturing. The above information is based on past history of the grade only and must not be construed as a guarantee of performance. Follow equipment manufacturer's recommendations for performance level and viscosity grade. The

Material Safety Data Sheet for this product is available from your nearest Gulf Distributor. Gulf Oil International

The information contained herein is believed to be correct at time of publication. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of the products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

www.gulfoilltd.com